


THIS DETAIL AND CONCEPT ARE THE PROPERTY OF DIVERSIFIED FALL PROTECTION, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT WRITTEN CONSENT OF DIVERSIFIED FALL PROTECTION, INC. OF CLEVELAND, OHIO.

## 5,000 lb CAPACITY ROOF ANCHOR

SCALE: 3"

REQD ( )



### STRUCTURAL STEEL: MATERIAL & FINISH:

1. 3 COAT SHERWIN WILLIAMS ENAMEL, 10 MILS TOTAL
2. SAFETY YELLOW
3. A36 PLATE AND A500 HOT ROLLED STEEL

### HARDWARE & ANCHORAGE CONNECTOR - MATERIAL & FINISH

1. ANCHORAGE CONNECTOR: FORGED, 10K, YELLOW DICHROMATE WITH LEACH BACK AND SEALANT FINISH.
2. ANCHORAGE HARDWARE: GR8 HEAT TREATED HS BOLTS, CHROMATE/DICHROMATE FINISH.

	<b>DIVERSIFIED FALL PROTECTION, INC.</b> <small>Division of K &amp; D Diversified Products, Inc.</small>		
	<small>15752 Industrial Parkway  Cleveland, OH 44135-3099  Phone: 216-295-2862  Fax: 216-433-0110  Web: www.fallprotect.com  E-Mail: info@fallprotect.com</small>		
CLIENT:			
PROJECT DESCRIPTION: SINGLE POINT ANCHOR (SPA) SPA4518Y			
DRAWING TITLE: STANDARD DETAIL			
DRAWN BY: B HEANEY	DATE:	PROJECT NO.	DWG NO. SPA-S1.
CHECKED BY:	DATE:	SCALE: AS NOTED	REV 0
OTHER:	DATE:	SHEET 1 OF 1	