


THIS DETAIL AND
CONCEPT ARE THE
PROPERTY OF
DIVERSIFIED FALL
PROTECTION, INC. AND
SHALL NOT BE
REPRODUCED, COPIED
OR USED IN ANY
MANNER WITHOUT
WRITTEN CONSENT OF
DIVERSIFIED FALL
PROTECTION, INC. OF
CLEVELAND, OHIO.

5,000 lb CAPACITY ROOF ANCHOR

SCALE: 3"

REQD ()




STRUCTURAL STEEL: MATERIAL & FINISH:

1. 3 COAT SHERWIN WILLIAMS ENAMEL, 10 MILS TOTAL
2. SAFETY YELLOW
3. A36 PLATE AND A500 HOT ROLLED STEEL

HARDWARE & ANCHORAGE CONNECTOR - MATERIAL & FINISH

1. ANCHORAGE CONNECTOR: FORGED,
10K, YELLOW DICHROMATE WITH LEACH
BACK AND SEALANT FINISH.
2. ANCHORAGE HARDWARE: GR8 HEAT TREATED HS
BOLTS, CHROMATE/DICHROMATE FINISH.

	DIVERSIFIED FALL PROTECTION, INC. <small>division of K & D Diversified Products, Inc.</small>		
	<small>15752 Industrial Parkway Cleveland, OH 44135-3389 Phone: 216-285-2862 Fax: 216-433-0110 Web: www.fallprotect.com E-Mail: info@fallprotect.com</small>		
CLIENT:			
PROJECT DESCRIPTION: SINGLE POINT ANCHOR (SPA) SPA4518Y			
DRAWING TITLE: STANDARD DETAIL			
DRAWN BY: B HEANEY	DATE:	PROJECT NO.	DWG NO. SPA-S1.
CHECKED BY:	DATE:	SCALE: AS NOTED	REV 0
OTHER:	DATE:	SHEET 1 OF 1	