

Permanent, durable fall protection

Permanently secure roof lines with the Gen2 Warning Line System. This compact, non-penetrating concrete base design protects your rooftop surface while standing up to the elements for a weather-resistant, long-lasting safety solution.



Elevating safety standards FallProtect.com

Details

- Galvanized steel stanchion posts and fittings
- Heavy-duty molded plastic warning flags
- Aluminum top cap set screw design secures warning line
- OSHA 1910.29(d) and 1926.502(f) (2) compliant
- Kit Includes 25 feet of plastic coated steel cable and 4 yellow warning flags



Represented by:

Fast installation

The Gen2 system installs quickly and securely. Use these simple steps to set up your warning line system:

- Install intermediate base plate and stanchion assembly at 24-foot intervals, with corner post assemblies and end post assemblies as needed
- Guide cable through each top cap and secure with set screw
- Place warning flags at 6-foot intervals

Specifications

- Stanchion assembly height: 39"
- Base dimensions: 14" x 14" 4"
- Intermediate base weight : 62 lbs.
- End/Corner base plate weight: 124 lbs.

Available options

Order by part number.

PART NUMBER	DESCRIPTION
WL-GEN2-02	Intermediate post kit
WL-CORNEROUT-02	Corner outrigger post kit
WL-ENDOUT-02	End outrigger post kit



Elevating safety standards FallProtect.com

24400 Sperry Drive Westlake, OH 44145

For more information, talk to a fall protection specialist at (800) 504-4016.