

EZ Series Roof Ladder

Safe, Durable, and OSHA-Compliant
Access Solutions



The EZ Series Fixed Access Ladder is designed to provide OSHA-compliant safety and easy access to roofs, platforms, and walkways. Built to accommodate one user at a time, this system offers a robust 800-lb load capacity while meeting OSHA 1910.23(d) and ANSI standards. Consult with a qualified engineer to confirm structure supporting ladder is capable of supporting ALL intended loads applied to ladder when in use.

Important Measurements

- **Climbing width:** Must be a minimum of 16 inches- OSHA 1910.23(b)(4)
- **Stand-off distance:** 7 inches minimum must be measured from the midpoint of the ladder rung to the nearest permanent object in back of the ladder. OSHA 1910.23(d)(2).
- **Top Rung Clearance:** The top rung of the ladder must be either in line of below the roof and no more than 12" below.

Additional Fall Protection Accessories

For ladders exceeding 24 feet, a fall protection system is mandatory per OSHA 1910.28(b)(9). Diversified Fall Protection offers the following ladder systems:

- Safety Swing Gates
- Bolt On Walk Throughs
- Ladder Guards
- P>Returns
- Ladder Lifeline Systems
- Parapet Crossovers & Step Systems

Features

- Rung Width: 20"
- Walk through: 30"
- Standoff Brackets: Bolt on, with vertical/horizontal adjustability
- Floor/Bottom mount available
- Side Rail Construction: 3" Flat Stock
- Hot dipped galvanized finish
- 10' maximum modular sections reduce freight costs